

**TOWN OF QUEEN CREEK** Public Works Department Traffic Engineering Program 22358 S. Ellsworth Road Queen Creek, Arizona 85242

## TRAFFIC SIGNAL, ITS AND STREET LIGHTING APPROVED MATERIALS LIST

Revised Mar 2023

ltem	Approved Manufacturer / Model	
Cabinet and Controller Assembly	<ul> <li>Econolite Cobalt \ TS2</li> <li>Econolite Plug-n-Go Cabinet Assembly (per TOQC typ. configuration)</li> <li>ADOT Type V, NEMA TS2, Type 1</li> <li>16 load switch positions w/ 16 load switches provided (unless otherwise noted)</li> <li>Exterior generator power input plug</li> <li>Econolite SHA300-10 (31637P4) surge suppressor</li> <li>Manual control handheld remote ("pickle switch") with detachable headphone jack connection in police panel (per TOQC typ. configuration)</li> <li>Battery backup – ZincBlue 2 with two 500W battery</li> <li>EXCLUDE railroad pre-emption panel (unless otherwise noted)</li> </ul>	
Malfunction Management Unit	Eberle Design Inc. (EDI) MMU-16LEip SmartMonitor	
Meter Pedestal	MYERS MEUG3A-2050 -M100-AZ (MOD) (or approved equal)	
Video Detection	Autoscope Vision, Each intersection shall have (1) spare camera and mounting assembly	
Emergency Vehicle Pre- emption	Tomar STROBECOM II – 4090-21-ST1IC-X series detectors, 4140 optical signal processor card with 4 channels, M913 detector cable (or approved equal)	
Traffic Signal Poles (w/ anchor bolts), Signal Mast Arms, Luminaire Mast Arms	ADOT Standard Design (2013)	
Vehicular and Pedestrian Traffic Signal Heads	Traffic Control Technologies, McCain Traffic Supply, 3M Corp., Eagle, Econolite, Peek Traffic Systems (aluminum only)	
Traffic Signal Lamp	Dialight XL15-series LED (or approved equal)	
Pedestrian Signals	Dialight X-series Uniform Appearance LED Countdown Signals (16x18), GE Lumination GT1 LED Countdown Signals (16x18), Excellence Opto. Inc. Countdown Signals (16x18) – all pedestrian modules shall meet the minimum ITE specification.	

Pedestrian	Polara, Bull Dog – With Town logo etched into button
Push Buttons	Each intersections shall have (2) spare Push Buttons
Pedestrian	Layout per ADOT Manual of Approved Signs, Code R10-3eAZ.
Push Button	Automatic Signal / Eagle Signal, McCain Traffic Supply, Pelco
Signs	Products, Inc., Traffic Parts, Inc., Traffic Signal Hardware
Vehicular and Pedestrian Mounting Hardware	Econolite, McCain Traffic Supply Hardware, Automatic Signal / Eagle Signal, Pelco Products, Inc., Traffic Parts, Inc., Traffic Signal Hardware, Peek Traffic Systems, Inc.
Intersection Lighting Luminaires	GE Evolve LED Roadway Scalable Cobrahead
w/ Lamp	All luminaires shall have shorting caps installed.
Photo Electric Controls (w/ delay)	Fischer Pierce (or approved equal)
	ADOT No. 7 and smaller – Christy Fiberlite, Christy Fiberlite lid
Pull Boxes, Vaults and Lids	ADOT No. 9 – refer to engineering standard detail
Wire Marking Tape	3M Scotchkote Wire Marker Tape (or approved equal)
Wire Nuts (Silicone Filled)	IDEAL 451, 452 and 454 (or approved equal)
Conduit Warning Tape	Presco (or field-approved equivalent)
Illuminated Street Name Signs	Fluoresco Lighting & Signs, 8'-3/4"W x 30"H x 12"D cabinet (TOQC to approve <u>all layouts</u> prior to ordering)
Solar Powered School Flashers	Solar Traffic Controls (or approved equal) with wireless connection to nearest traffic signal control cabinet.
	Axis Q6075-E PTZ Dome Network Camera with smoked dome.
ссти	Each intersections shall have (1) spare camera and mounting assembly - T91L61.
Wireless	Encom Wireless – COMMPAKBB58N2INT 5.8 GHz integrated wireless radio (300 Mbps)
	( A wireless radio system requires two radios or more)
Fiber Optic Splice Enclosure	Tyco Electronics 450 Fiber Optic Gel Splice Closure, or as required by the Town Traffic Engineering group.# 450-D6-6-NT-0-D6V
	Splice Tray Kit #FOSC-ACC-D-TRAY-72-KIT
Gator Patch	Fiber Connections #G620J012LNB-Y-Z 12 fiber Gator Patch ITS drop cable.

Ethernet switch	Ruggedcom (model# 6GK6092-0PS23-0CA0-Z-A05-B05-C05- D05) with four single mode, 1300nm, 25km SFP's (99-25-0101 = 1000LX SFP, Single mode, LC, 1310nm, 25 km). With External power supply Ruggedcom RPS 1300 and Din Rail mount (#6GK6000-8MS00-0AA0)
	And (16) Cat5e (350 MHz) Blue Molded Patch Cables RJ45 (Male/Male) – 6ft. (4) LC to SC Singlemode Duplex jumper 2 meters long.
Geotextile inner duct	Maxcell 3"-3 cell detectable Maxcell 2"-3 cell detectable

## Notes:

- 1. The Town reserves the right to modify this list, to reject items included on the list, and/or to accept items not included on the list, at any time, without prior notice, if determined necessary in the best interests of the Town.
- 2. Products not covered by this list shall be submitted to the Town for review and approval prior to ordering.
- 3. Brand names listed may be registered trademarks of their respective manufacturers.